

BLIZZARD 5-22																
Max. Heating Capacity (kW)																
	Ambient Temperature (°C)															
Water outlet(°C)	-28	-25	-20	-15	-10	-7	-5	2	7	10	15	20	25	30	35	43
25	9.10	11.50	12.40	13.70	15.60	16.50	17.20	18.00	22.00	22.70	23.72	25.78	24.66	24.20	23.00	23.90
35	9.18	11.50	12.40	13.70	15.63	16.50	17.20	18.00	22.00	22.80	23.72	25.78	24.80	24.00	22.65	23.82
45	9.30	11.58	12.56	14.00	15.65	16.50	17.24	18.10	22.10	22.96	23.83	25.90	24.50	23.60	22.20	23.33
50	9.58	11.95	12.72	14.05	15.70	16.58	17.50	18.25	22.20	23.05	23.93	26.02	23.95	23.30	20.55	22.80
55	9.95	12.34	12.82	14.49	15.75	16.50	17.65	18.32	22.00	23.34	23.72	25.78	22.53	20.00	20.40	22.77
60	10.20	12.72	13.00	14.60	15.90	16.95	17.80	18.50	23.03	23.26	21.17	22.53	22.00	19.50	20.30	22.25
65	/	11.50	12.20	13.72	14.95	15.44	16.06	16.90	18.28	20.35	19.60	21.26	19.70	17.41	19.35	22.00
70	/	/	/	12.50	13.58	14.45	15.20	16.95	18.36	20.40	18.32	19.40	18.00	16.90	/	/
75	/	/	/	/	13.16	14.00	15.00	17.00	18.40	20.40	18.00	19.45	18.00	16.80	/	/
80	/	/	/	/	13.07	13.90	14.80	16.80	18.35	20.30	18.05	19.50	18.10	16.56	/	/
Power Input (kW)																
	Ambient Temperature (°C)															
Water outlet(°C)	-28	-25	-20	-15	-10	-7	-5	2	7	10	15	20	25	30	35	43
25	5.46	5.48	5.21	5.03	5.03	5.06	5.15	5.00	4.95	4.88	4.81	4.94	4.30	3.71	2.90	3.00
35	5.56	5.58	5.60	5.65	5.68	5.70	5.80	5.62	5.60	5.49	5.41	5.54	4.70	4.05	3.10	3.30
45	5.80	5.69	6.00	6.10	6.30	6.20	6.21	6.25	6.34	6.25	6.01	6.14	5.30	4.57	3.30	3.60
50	5.87	6.32	6.48	6.53	6.62	6.63	6.68	6.71	6.72	6.60	6.32	6.45	5.50	4.74	3.53	3.55
55	5.94	6.89	6.78	6.84	7.01	7.05	7.26	7.37	7.10	6.90	6.71	6.85	5.40	4.66	3.70	3.79
60	6.81	7.17	7.25	7.38	7.56	7.60	7.67	7.85	8.16	8.00	6.65	6.71	5.80	5.00	3.95	4.00
65	/	7.24	7.33	7.45	7.78	7.80	7.88	7.44	7.51	7.60	6.99	6.68	5.81	5.01	4.12	4.20
70	/	/	/	7.60	7.80	7.85	7.88	8.00	8.10	8.16	6.50	6.65	5.85	5.04	/	/
75	/	/	/	/	8.45	8.50	8.53	8.65	8.75	8.81	6.83	7.00	6.33	5.46	/	/
80	/	/	/	/	9.13	9.18	9.21	9.33	9.43	9.49	7.25	7.38	6.67	5.75	/	/
COP(kW/kW)																
	Ambient Temperature (°C)															
Water outlet(°C)	-28	-25	-20	-15	-10	-7	-5	2	7	10	15	20	25	30	35	43
25	1.67	2.10	2.38	2.72	3.10	3.26	3.34	3.60	4.44	4.65	4.93	5.22	5.73	6.53	7.93	7.97
35	1.65	2.06	2.21	2.42	2.75	2.89	2.97	3.20	3.93	4.15	4.38	4.65	5.28	5.92	6.83	7.22
45	1.60	2.03	2.09	2.30	2.48	2.66	2.78	2.90	3.49	3.67	3.96	4.22	4.62	5.17	6.03	6.48
50	1.63	1.89	1.96	2.15	2.37	2.50	2.62	2.72	3.30	3.49	3.79	4.03	4.35	4.91	6.20	6.52
55	1.68	1.79	1.89	2.12	2.25	2.34	2.43	2.49	3.10	3.38	3.53	3.76	4.17	4.30	5.73	6.01
60	1.50	1.77	1.79	1.98	2.10	2.23	2.32	2.36	2.82	2.91	3.18	3.36	3.79	3.90	5.28	5.56
65	/	1.59	1.66	1.84	1.92	1.98	2.04	2.27	2.43	2.68	2.80	3.18	3.39	3.48	4.70	5.24
70	/	/	/	1.64	1.74	1.84	1.93	2.12	2.27	2.50	2.82	2.92	3.08	3.35	/	/
75	/	/	/	/	1.56	1.65	1.76	1.97	2.10	2.32	2.64	2.78	2.84	3.08	/	/
80	/	/	/	/	1.43	1.51	1.61	1.80	1.95	2.14	2.49	2.64	2.71	2.88	/	/

